

MGTP 160 SSF

Ready to Rent 160kVA Diesel Generator



When looking for a robust, reliable, good quality 160kVA rental-friendly generator, our MGTP 160 SSF has everything the hire market requires.

Optional extras: GPS Telemetry Tracker



IVECO
1 Year Engine Warranty (Limited)

Features

Benefits

- 160kVA 3ph AC Aux Power (400V)
- Linz alternator
- FPT (Iveco) diesel engine
- HVO (Hydrotreated Vegetable Oil) fuel approved
- Exclusive MHM-Gen engine protection shutdown system
- 3 way fuel valve
- 12V battery isolator switch
- Emergency stop button
- Variable RCD
- ELR bypass switch (activated by key only)
- Central lifting eye and fork pockets
- Fully bunded base
- Engine oil drain pump

- Plenty of power to meet the demands of medium to large generator hire
- Heavy duty and proven reliability
- World class performance and watercooled
- Suitable to run off either diesel, HVO or a mixture of both fuels
- In the case of low fuel, low oil pressure, high engine temp and battery charge failure
- Easy connectivity to an external fuel tank
- Reduces flat battery breakdowns
- A must on any UK site
- Flexible protection
- Turn off the ELR to avoid nuisance tripping when powering electrical motors
- Flexible and safe lifting on site
- To retain all spilt fluids
- Reducing service time



Specification

Performance

Alternator	Linz (AVR Controlled)	Three Phase Power (400V)	154kVA/ 123kW
Single Phase Power (110V)	N/A	Noise Level	LWA=88 dBa@7m=63
Single Phase Power (230V)	53kVA/ 42kW	Insulation Class	H
		Mechanical Protection - IP	23

Engine

Make	FPT (Iveco)	Fuel Consumption @ 75% Load (Litres/hour)	27.5
Type	NEF67TE1PV	Fuel Tank Capacity (Litres)	450
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Average Runtime (Hours)	
Number of Cylinders	6	@ 100% Load	13
Power (HP)	TBA	@ 75% Load	17
Engine Speed (RPM)	1500	@ 50% Load	23
Cooling	Water	@ 25% Load	27
		CO ₂ Per Hour @ 75% Load	72.05kg
		Control Panel	Deepsea 7310 c/w two wire Auto Start/ Stop facility

Dimensions (Machine only)

Length: 3270 mm	Width: 1350 mm	Height: 1945 mm
Dry Weight (No Fuel): 2400 kg		Wet Weight (Fuel Full): 2850 kg

Socket Configuration	3ph (400V)				1ph (230V)	
	125A	63A	32A	16A	32A	16A
MGTP 160 SSF	1	1	1	-	4	2

Hard wire facility	3ph (400V)	1ph (230V)
	MGTP 160 SSF	✓

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk