

POWER TOWER

LOW-LEVEL ACCESS



KEY SPECIFICATIONS

Platform carrying capacity:

250 kg

Dimension:

1.62 m x 0.78 m

Working Height:

5.10 m

Total Weight:

365 kg

KEY FEATURES

- 3.10 m platform height, 5.10 m working height
- 250 kg safe working load (1 person)
- Compact - only 0.78 m wide, passes easily through standard doorways
- Large 1.52 m x 0.75 m platform size
- Only 1.62 m x 0.78 m working footprint
- Easy access gate

STANDARD SPECIFICATIONS

Performance

Maximum working height	5.10 m
Maximum platform height	3.10 m
Closed platform height	0.74 m
Working outreach	0.65 m
Platform dimensions L x W	1.52 m x 0.75 m
Working foot print	1.62 m x 0.78 m
Safe working load	250 kg
Maximum manual force	200 N
Maximum gradient for operation	0.5°
Maximum wind force	Internal use only 0 m/s
Power sound level	Less than 70 dBA
Maximum castor point load	215 kg / 2.11 kN
Maximum wheel force	215 kg / 2.11 kN

Closed dimensions

Length	1.62 m
Width	0.78 m
Height	1.85 m
Weight	365 kg

Power options

Battery	12V c/w automatic charger
Mains	110V or 230V
Controls	Simple push button basket controls.
Construction	Heavy duty fabricated steel superstructure, stainless steel bushed pivots, tough powder coated finish.
Safety	CE marked, complies with applicable European legislation including the Machinery Directive using the EN280 design standard. Full fail-safe hydraulics, automatic locking wheels.
Options	Narrow basket for suspended ceiling grid access.

STANDARD FEATURES

- Footprint (1.62 m x 0.78 m)
- Optimal width to fit through single doorways
- Large platform (1.52 m x 0.75 m)
- Simple push button controls from platform
- Quality steel construction
- Durable powder coated finish
- Fail safe hydraulic circuit
- Emergency lower from ground level
- Acoustic signal when lifting and lowering
- Auto-lock brake on elevation
- Spirit Level
- Battery charge indicator

ACCESSORIES & OPTIONS

- Plug - 230V 2P EURO
- Plug - 110V 3P UK
- Plug - 230V 3P UK
- Plug - US STYLE for Latin America
- Tool Tethering options

IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



JLG EMEA BV

Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel.: +31 (0)23 565 5665
www.jlg.com

An Oshkosh Corporation Company